

# Berland

S u p p l y

Berland Supply 87 Healy Rd Cold Spring, NY 10516

## NM PEDESTAL



### SPECIFICATIONS

PRODUCT NAME:	NM
CHARACTERISTICS:	Polypropylene
ENVIRONMENTAL IMPACT:	Recyclable material - non dangerous
APPLICATIONS SURFACES:	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA :	Usable with any prefabricated self sustaining element for exterior flooring
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE*:	29.57 KN
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE*:	16.75 KN
SLOPE CORRECTION:	0-5%
SHORE:	70 (+/-3)
FIRE REACTION*	UNI EN 13501-1:2009 class E
LOW TEMPERATURES REACTION*:	-40

\*Calculated at medium hgt, between minimu and maximum extension

\*Tests made by Civil and Environmental Dept of U of Padova. 1 KN = 98,6 Kg

\*Tests made by Giordano S.p.A. Institute of Bellaria-Igea Marina (RN)-Italy

### ETERNO NM ADJUSTABLE PEDESTAL BENEFITS

- Adjustable pedestal for raised floors with adjustable height
- Base has holes for drainage and 4 precut lines to help facilitate any cutting of base.
- Slope compensator option on bottom self leveling reduces slope automatically up to 2%.
- Product is high and low temperature resistant
- Wide pedestal base for stabilization
- Adjustment key levels without removing paver saving 30-40% labor costs !!
- Precut tabs for easy removal
- Anti noise and anti slip head
- Resistant to weathering , acid, UV rays
- Fully recyclable

### DIMENSIONS

Characteristics	Value
Base Diameter	8"
Head Diameter	6"
Minimum Height	1 1/2"
Maximum height	21 3/4"
Tabs Thickness	1/8"
Tab Height	1/2"
Weight	.97 to 1.23lbs

